



BROCHURE

NEW

Oil Level Alarm OLA400

Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover 12 key areas:

- Lifejacket Lights
- Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
 - Special Lights
 - LED Flares
- Forward Looking Sonars (FLS)
 - Bridge Navigational Watch Alarm System (BNWAS)
 - Salinometers
 - Oil Level Alarm
 - Electronic Inclinometer
- Agency for a range of world-renowned safety product brands (supplied to the Danish market)

Further Information

For further information on our products, please see our website: www.daniamant.com



Function

The Oil Level Alarm OLA400 can, when installed in a boiler system's hot well, detect the occurrence of potentially critical oil. If oil is detected a visual alarm indication will be shown on the control box and further relays are available to output the alarm to any central alarm system.

Typical Use

The most critical water contamination in a ship's boiler system is oil entering the steam or condensate from leaking tank coils or heat exchangers. The boiler could be completely destroyed due to overheating of the furnace.

The hot well can easily be equipped with OLA400 which will continually detect oil occurrence. This can ensure that oil can be detected before it enters the feedwater section.

Mains Supply

85-265 VAC, 50-60 Hz, and 24 VDC (+12/-6 VDC).

Mains Current

Mains supply must be secured against overcurrent externally.
Max. 100mA for 115-230 VAC supply.
24 VDC must be secured against overcurrent externally with a fuse of maximum 250 mA.

Power Consumption

Max. 3.5 W

Build in Test-Function

Self-test on start up.

Response Time

Approx. 20 sec. (adjustable)

Alarm Level

ON/OFF

(All specifications are subject to change without notice)



OLA400



Sensor unit

Daniamant A/S
 Industrivej 24C
 3550 Slangerup
 Denmark

Tel +45 47 37 38 00
 Fax +45 47 37 38 09
 info@daniamant.com

Daniamant Ltd
 Unit 3, The Admiral Park
 Airport Service Road
 Portsmouth, PO3 5RQ
 United Kingdom

Tel +44 23 92 67 51 00
 Fax +44 23 92 67 51 01
 sales@daniamant.com

Sensor Disconnected

Alarm indicating an incorrect connection to the sensor or defective sensor unit.

Cable Connections

Terminal 1 - 5: Sensor unit
Terminal 6 - 8: Relay contacts for ALARM RELAY 1
Terminal 9 - 11: Relay contacts for ALARM RELAY 2
Terminal 12 - 13: 24 VDC supply
Terminal 14 - 15: Mains Supply

Relay Contacts

8A / 230 VAC. Relays must be protected by external fuses.

Ambient Temperature

0 – 55 ° Celsius (Oil Level Alarm Control Box)
 0 – 95 ° Celsius (Sensor Unit)

Pressure

Max. continuous operational pressure 2 bar. (Pressure safety limit 10 bar.)

Sensor Installation

$\frac{3}{4}$ " BPST thread.

Control Box Dimensions

W x H x D: 222 x 125 x 60mm

Control Box Rating

IP66/67

DNV-GL	
TYPE APPROVAL CERTIFICATE	
Certificate No: TAA000016	
This is to certify:	
Type: Oil level alarm	
with type: Oil Level Alarm (OLA) comprising control box and sensor unit	
Issued to:	
Daniamant Electronics A/S	
Slangerup, Denmark	
is issued in conformity with:	
DNV GL rules for classification - Ships, offshore units, and High speed and light craft	
Application:	
Product(s) approved by this certificate to be installed on all vessels covered by DNV GL:	
Location classes:	
Temperature	B
Humidity	A
Shock	A
Vibration	A
Enclosure	B / IP44
Issued at Malmö, SE 2017-04-03	for DNV GL
This Certificate is valid until 2022-04-03.	DNV GL local station: Copenhagen
Approval Engineer: Silke Steen	Odd Magne Hestegård Head of section
<small>This Certificate is issued to the manufacturer and not to the applicant. Changes to design or construction may void this Certificate unless the manufacturer notifies DNV GL. For more information, please refer to the DNV GL Rules for Classification - Ships, Offshore Units, and High Speed and Light Craft.</small>	
<small>DNV GL is a member of the DNV Group. For more information, please refer to the DNV GL website: www.dnvgl.com Page 1/1</small>	