

PRODUCT SAFETY DATA SHEET

**PRODUCTS: Rescue DAN M / Rescue DAN M1 / Rescue DAN W1 /
Rescue DAN MR / Rescue DAN WR / Rescue SOL / Rescue DAN R.INT1**

SECTION 1: IDENTIFICATION

PRODUCT NAME	Marine Safety Light Systems Rescue DAN M / DAN M1 / DAN W1 / DAN MR / DAN WR / SOL / R.INT1
MANUFACTURERS NAME	DANIAMANT LIMITED
ADDRESS TELEPHONE NO. FAX NO.	Unit 3, The Admiral Park, Airport Service Road, Portsmouth, Hants. PO3 5RQ UK +44 (0) 23 9267 5100 (Switchboard) +44 (0) 23 9267 5101 (Fax)
EMERGENCY NOS.	FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE EXPOSURE OR ACCIDENT CALL CHEMTREC DAY OR NIGHT: 00 1 703 527 3887 (SHIPMENT TO AND FROM USA) (CHEMTREC OFFICE) 800 424 9300 (INTERNAL N.AMERICA MOVEMENTS) (CHEMTREC OFFICE) D806 CHEMTREC COMPANY CODE 205617 COMPANY NUMBER
DESCRIPTION	Lithium powered marine safety light systems are designed to be stored for up to five years before use. The battery cells are hermetically sealed. Pressurised primary lithium/sulphur dioxide and as supplied are electronically protected by a fuse and from external environment by a moulded plastic casing. In this state the units constitute no definable hazard to health. However disassembly, abuse or destruction of the battery cell will expose the contents and the following Health and Safety Hazards.

SECTION 2: INFORMATION OF INGREDIENTS

HAZARDOUS COMPONENTS:					
	CAS NUMBER	EC Number	% OPTIONAL	OSHA/PEL	ACGIH TLV 5 TEL
Lithium Metal	7439-93-2	231-102-5	<3.3%		
PC Propylene Carbonate	108-32-4	203-572-1	<5%		
Manganese Dioxide	215-202-6	1313-13-9	<25%		
Carbon Black	1333-86-4	215-609-9	<6.5%		
DME 1,2-Dimethoxyethane	110-71-4	203-794-9	<2%		
DOL 1,3-Dioxolane	646-06-0	211-463-5	<4.3%		
LiAlClO ₄			<1.33%		
Reference : Sax's dangerous properties of industrial materials. NOTE: These products do not contain asbestos.					

SECTION 3: HAZARD IDENTIFICATION

LITHIUM METAL:	This is flammable when in contact with water. It reacts violently to produce hydrogen and lithium hydroxide. Use only soda ash, sodium chloride or graphite to extinguish flames.
MANGANESE DIOXIDE:	Poison by intravenous and intratracheal routes moderately toxic by subcutaneous route. Experimental reproductive effects. A powerful oxidiser, flammable by chemical reaction. Must not be heated or rubbed in contact with easily oxidizable matter.
DME	Experimental teratogen. Other experimental reproduction effects readily forms an explosive peroxide. A very dangerous fire hazard when exposed to flame, heat or oxidisers. When heated to decomposition it emits acrid smoke and fumes
LiAlClO₄	Moderately toxic. Skin, eye and mucous membrane irritant an oxidiser which is incompatible with nitromethane acetone hydrogen and oxygen. When heated to decomposition it emits very toxic fumes.

SECTION 4: FIRST AID MEASURES

EYES:	Irrigate thoroughly with water for at least 15 minutes. Obtain medical attention.
INHALATION:	Remove from exposure, rest and keep warm. In severe cases, or if exposure has been great, obtain medical attention.
SKIN:	Drench the skin thoroughly with water. Remove contaminated clothing and wash before re-use. Unless contact has been slight, obtain medical attention.
INGESTION:	Wash out mouth thoroughly with water and give plenty of water to drink. Obtain medical attention.
FURTHER TREATMENT:	All cases of eye contamination, persistent skin irritation and casualties who have swallowed this substance or been affected by breathing its vapours should be seen by a doctor.
EMERGENCY AND FIRST AID PROCEDURES:	If cell vents, personnel should be evacuated from contaminated areas. Other materials are either inert or have low hazard associated with their exposure.

SECTION 5: FIRE FIGHTING MEASURES

If cells are directly involved in a fire, DO NOT USE SAND, DRY POWDER OR SODA ASH, GRAPHITE, METAL CLASS D EXTINGUISHERS OR A FIRE BLANKET. Copious quantities of a water based foam is the only recommended extinguishing media for fires involving cells. IF a fire is in an adjacent area, and cells are packed in their original containers, the fire can be fought based on fuelling material e.g. paper and plastic products. Avoid fume inhalation.

In the case where significant quantities of lithium / sulphur dioxide batteries have been involved in a fire, account must be taken of the possibility that flammable gases might be evolved should water come into contact with the cold battery residues. These gases might include Acetylene, Hydrogen and Cyanide. It is recommended that ventillation should be maximised should this scenario be realised.

EXTINGUISHING MEDIA: Copious quantities of a water based foam.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Do not breathe vapours or touch liquid with bare hands. If the skin has come into contact with the electrolyte it should be washed thoroughly with water. Earth or sand should be used to absorb the exudation, seal leaking battery and earth in a heavy-duty polythene bag and dispose of as special waste.

SECTION 7: HANDLING AND STORAGE

Handle and store in cool, well-ventilated area. Keep out of direct sunlight and away from heat sources.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDLING	Do not short circuit or expose to temperatures above the temperature rating of the battery. Do not recharge, over-discharge, force discharge, immerse, puncture or crush.
STORAGE	Store in a cool place but prevent condensation on cells and batteries. Elevated temperatures can result in shortened battery life and degrade performance. Do not store batteries in high humidity environments for long periods. External corrosion of the Nickel plated can and tags could result in the formation of toxic metal salts. Avoid ingestion, observe personal hygiene wash hands after contact.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Light in a plastic housing.
ODOUR	If leaking, smells of medical ether.
STABILITY IN WATER	Product is waterproof.
REACTION WITH WATER	Only if damaged.
FLASH POINT	Not applicable unless individual components exposed.
FLAMMABILITY	Not applicable unless individual components exposed.
RELATIVE DENSITY	Not applicable unless individual components exposed.
SOLUBILITY IN WATER	Not applicable unless individual components exposed.
SOLUBILITY OTHER	Not applicable unless individual components exposed.

SECTION 10: STABILITY AND REACTIVITY

Hazardous materials are housed within a hermetically sealed unit, under normal conditions this unit is Non-Hazardous.

HAZARDOUS REACTIONS	Lithium metal reacts with water to produce highly flammable gasses.
HAZARDOUS DECOMPOSITION REACTIONS	Toxic fumes, and may form peroxides.

SECTION 11: TOXICOLOGICAL INFORMATION

SIGNS & SYMPTOMS	NONE, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Over-exposure can cause symptoms of non-fibrotic lung injury and membrane irritation.
INHALATION	Lung irritation.
SKIN CONTACT	Skin irritation.
EYE CONTACT	Eye irritation.
INGESTION	Tissue damage to throat and gastro/respiratory tract if swallowed.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE.	In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur.

SECTION 12: ECOLOGICAL INFORMATION

MAMMALIAN EFFECTS	None known at present.
ECO-TOXICITY	None known at present.
BIOACCUMULATION POTENTIAL	Slowly bio-degradable.
ENVIRONMENTAL FATE	None known environmental hazards at present.

SECTION 13: DISPOSAL

DISPOSAL	DO NOT INCINERATE, or subject cells to temperature in excess of 90°C. Such abuse can result in loss of seal, leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations. DO NOT ATTEMPT TO DISMANTLE THIS PRODUCT.
-----------------	--

SECTION 14: TRANSPORT INFORMATION

UN Hazard Code	Class 9
UN Number	3091
UN Proper Shipping Name	Lithium Metal Batteries Contained in Equipment.
IATA Packing Instructions for air	970, Section II
Packing instructions for road and sea	Special Provision 188 & 230
Lithium Content	0.99g (≤ 1 gram lithium metal cell)
Labelling	As per IATA, IMDG & ADR requirements - Precautionary label

Battery Test Criteria	Tested to UN ST/SG/AC.10/11/Rev.5/Amend.1 Criteria III Section 38.3. (Test Certificate available on request). Each cell and battery incorporates a safety venting device. Each cell and battery is equipped with an effective means of preventing external short circuits and reverse current flow.
------------------------------	--

SECTION 15: REGULATORY INFORMATION

Classification	Class 9	
Hazard Symbol	N/A	
Risk Phrases	R11 R14/15 R21 R22 R36/37 R35 R41 R42/43	Highly flammable Reacts violently with water liberating extremely flammable gases Harmful in contact with skin Harmful if swallowed Irritating to respiratory system. Causes burns. Risk of serious damage to the eyes May cause sensitisation by inhalation and skin contact.
Safety Phrases	S2 S8 S22 S24 S26 S36 S37 S45	Keep out of the reach of children Keep away from moisture Do not breathe dust Avoid contact with skin In case of contact with eyes, rinse immediately with plenty of water Wear Suitable protective clothing Wear Suitable gloves In case of incident, seek medical attention

SECTION 16: OTHER INFORMATION

Disclaimer	This PSDS is provided for information only The information and recommendations set forth herein are made in good faith and are believed to be accurate as of the date of preparation. However the company makes no warranty, either expressed or implied with respect to this information and disclaims all liability from reliance on. It is the shippers responsibility to ensure that they are trained and competent in handling and shipping lithium batteries by all transport modes.
-------------------	--

07 October 2019