



BROCHURE

**ODEO** DISTRESS FLARE

**NEW**

## Odeo Distress LED Flare (eVDSD)

Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

### Daniamant products cover 12 key areas:

- Lifejacket Lights
- Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
  - Special Lights
  - LED Flares
- Forward Looking Sonars (FLS)
- Bridge Navigational Watch Alarm System (BNWAS)
  - Salinometers
  - Oil Level Alarm
- Electronic Inclinator
- Agency for a range of world-renowned safety product brands (supplied to the Danish market)

### Further Information

For further information on our products, please see our website: [www.daniamant.com](http://www.daniamant.com)

### Introduction

Daniamant is proud to introduce the ODEO Distress as the next generation of Electronic Visual Distress Signal Device (eVDSD). As the world starts to embrace LED technology in place of traditional pyrotechnic flares Daniamant have built on the ground breaking ODEO Flare design and improved the product once more.

New standards and regulations are still being discussed at the USCG and RTCM; these will result in an alternative standard to replace pyrotechnics. Whilst this work proceeds in the background, Daniamant thought that our Customers should be able to take advantage of technology advances in the interim.

### Function

Traditional flares will illuminate for around 30 seconds before extinguishing, the Odeo Distress illuminates for around 8 hours at full illumination. Because no pyrotechnics are used, the Odeo product range is totally safe when switched off, and because it uses battery power (high power Lithium or Alkaline cells), it can even be safely posted or carried in baggage on flights.

### Major Benefits

- No heat, no flames, no risk
- No explosive compounds for shipping or disposal
- Increased Safety
- Longer operating life – now 8 hours 25% more than the ODEO Mk3
- Supplied with lanyard
- Search and Rescue aircraft safe
- Ideal for diving; tested to 50 meters for 1 hour
- Floats
- Easy user battery change
- Now includes IR LED for NVG search and rescue
- SoS Signal built in
- Small compact design (grab bag item)
- Simple activation (with wet or gloved hand)
- Dual function including flicker and SoS strobe





**Daniamant Ltd**  
 Unit 3, The Admiral Park  
 Airport Service Road  
 Portsmouth, PO3 5RQ  
 United Kingdom

Tel +44 23 92 67 51 00  
 Fax +44 23 92 67 51 01  
 sales@daniamant.com

**Daniamant A/S**  
 Industrivej 24C  
 3550 Slangerup  
 Denmark

Tel +45 47 37 38 00  
 Fax +45 47 37 38 09  
 info@daniamant.com  
 orders@daniamant.com

### Typical Use

Whilst originally designed for marine use, its lightweight, safe performance means that it is incredibly useful for any outdoor activity. The smaller size makes the ODEO Distress ideal for mountaineering, skiing, kayaking, expeditions etc. - any activity that can benefit from the added safety and security of carrying a distress flare - without the unwanted dangers. The ODEO Distress small size and waterproof rating IP68 (50m) also makes it an ideal safety device for divers.

### Power Supply

The Odeo Distress uses either 4 x L91 Lithium batteries or 4 x Alkaline batteries. These batteries have the required shelf life and power capacity and will operate over an extended temperature range.

### Regulations

The Odeo Distress is designed with consideration to SOLAS requirements, making it a genuine alternative to the pyrotechnic red hand held flare. The US Coast Guard is now leading the world in developing standards for electronic Visual Distress Signal Devices (eVDSD's) as a replacement for the hand held pyrotechnic flare. The Odeo Flare™ also outputs an SOS signal during its flash pattern as described in Annex 4 to COLREGS, and is thus an internationally recognised distress signal.

### Performance Comparison

